


## Subconn PUR Cable

## Type D/P4TP24#SW



Document no.	2013026SC
Revision	D
Date	18.11.2020
Prepared by	VSK
Approved by	SB

### Construction Characteristics

<b>Twisted pairs</b>	0,25 mm <sup>2</sup> (#24AWG) stranded tinned copper wires 19/.005, twisted together, insulated with Polypropylene, approx. 0,35 mm wall thickness (4 off)
<b>Filler</b>	Rod filler for roundness
<b>Binder</b>	An overall clear tape wrap
<b>Outer jacket</b>	Polyurethane jacket. 85A Shore Hardness. Color black. Nominal thickness approx. 1,27 mm
<b>Color Code</b>	Twisted pair #1: Brown & White/Brown Twisted pair #2: Blue & White/Blue Twisted pair #3: Orange & White/Orange Twisted pair #4: Green & White/Green
	The cable is Halogen free

### Mechanical Characteristics

<b>Diameter</b>	Nom. 9,65 mm
<b>Weight in air</b>	82 kg/km
<b>Weight in seawater</b>	6 kg/km
<b>Minimum bending radius</b>	102 mm
<b>Depth rating</b>	300 m

### Electrical Characteristics

<b>Operating voltage</b>	300 V
--------------------------	-------